

2311

INCHES

.39
[9,9]1.25
[31,8]1.06
[26,9].50
[12,7].55
[14].78
[19,8].50
[12,7]1.25
[31,8]AXIAL
LOAD
DIRECTIONSUPPORTED
MEMBER

WASHER

SUPPORTING
MEMBER.186
[4,72]

WASHER

Ø .78
[19,8]

PART NUMBER

MAX. AXIAL
DEFLECTIONMAX. AXIAL
LOAD

NATURAL RUBBER	NEOPRENE	in	mm	lb	N
2311-700	2311-800	.05	1.27	50	222
2311-70	2311-80			60	267
2311-71	2311-81			80	356

RECOMMENDED BOLT
INFORMATION

ENGLISH		METRIC		CLAMP LOAD		TIGHTENING TORQUE	
SIZE	GRADE	SIZE	CLASS	lb	N	ft-lb	N-m
3/8	5	M8	9.8	4941	21979	30.9	41.72

TIGHTENING TORQUE

WASHER SPECIFICATIONS

O.D.		I.D.		THICKNESS	
in	mm	in	mm	in	mm
1.5	38.10	.40	10.16	.134	3.40



TITLE: 2311	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF EBCO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF EBCO IS PROHIBITED.	
TOLERANCES PER RMA STANDARD A3	REV. A
DATE: 9-3-13	UNITS INCH [MM]
1330 HOLMES RD. ELGIN, IL 60123	

SPECIFICATIONS SUBJECT TO CHANGE